

Mounter and Demounter, Tire

NSN: 4910-01-370-9855
LIN: M76101
TM: Commercial

System Description

This is a stationary, power-driven, tire mounter-demounter. The electrical system is designed to operate from 220 Volt, 50/60 Hertz, Single Phase on 5 kw or less of power, and the motor Single Phase on 5 kw or less power.

System Mission

It is capable of mounting and demounting both tube and tubeless tires and shall be able to accommodate minimum wheel diameter of not more than 15 inches, maximum wheel diameter of not less than 44 inches, maximum wheel width of not less than 40 inches and maximum tire diameter of not less than 83 inches.

This system is not currently in reset.

Reset Type

Reset Work (Field Level) - Work performed to correct equipment faults that are performed at the ORG/DS level; performed by unit level soldiers, augmented by contractor as required.

Reset Strategy

It is a field level repairable item; no maintenance repair program currently exists. Item is a supply class 2, AWCf item and units should submit a funded requisition to B14 to acquire the Mounter/Demounter. This item can be reconstituted by contacting the manufacturer, Capitol Logistics LLC. Phone 301-493-8674 or FAX 301-493-9077. One year warranty from date of purchase.

Reset Responsibility

Unit

Reset Location

This system is not currently in reset.

- Contact Information -

877.4.PMSKOT (877.476.7568)
rock-pm-skot@conus.army.mil